

## Synthoil Race Tech GT1 SAE 10W-60

### DESCRIPTION

Synthoil Race Tech GT1 SAE 10W-60 is a modern, fully synthetic, high-performance engine oil formulated for use in four-stroke engines under extreme load. The combination of synthetic base oils and modern additive technology satisfies the requirements of the latest engine designs.

### PROPERTIES

- optimum lubrication under extreme conditions
- very high lubrication and ageing stability
- extremely low oil consumption and evaporation loss
- outstanding engine cleanliness
- rapid oil delivery at low temperatures
- miscible and compatible with commercially-available engine oils.
- tried and tested with exhaust catalytic converters

### Specifications / Approvals:


API SL/CF

### TECHNICAL DATA

Basis	:	Synthetic oil/additives
Viscosity class	:	10W-60
ASTM colour	:	3.5
Density at 15 °C	:	0.86 g/cm <sup>3</sup>
Viscosity at 40 °C	:	163 mm <sup>2</sup> /s
Viscosity at 100 °C	:	24 mm <sup>2</sup> /s
Viscosity index	:	179
Flash point	:	238 °C
Pour point	:	-35 °C
Evaporation loss	:	6.9 %

### APPLICATION

For petrol and diesel engines with and without turbocharging. Especially suitable for extreme engine requirements and racing.



# PRODUKTINFORMATION



## INSTRUCTIONS

The operating instructions of the vehicle and engine manufacturers must be followed.


## AVAILABLE PACK SIZE

Synthoil Race Tech GT1  
SAE 10W-60

1 l	Part no. 1390 D-GB-I-E-P
1 l	Part no. 1943 D-RUS-UA
1 l	Part no. 8908 D-NL-F-GR-ARAB
5 l	Part no. 1391 D-GB-I-E-P
5 l	Part no. 1944 D-RUS-UA
5 l	Part no. 2876 D-DK-FIN-N-S
5 l	Part no. 8909 D-NL-F-GR-ARAB
20 l	Part no. 1392
60 l	Part no. 1393
205 l	Part no. 1394
lose Ware	Part no. 1399

PI 07/07/11

**Our information is based on thorough research and may be considered reliable, although not legally binding.**



LIQUI MOLY GMBH  
Jerg-Wieland-Str. 4  
D-89081 Ulm-Lehr

Postfach 28 29  
D-89018 Ulm  
www.liqui-moly.de

Phone: +49-(0)731/1420-13  
Fax: +49-(0)731/1420-82  
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230  
Technische Hotline: +49-(0)731/1420-13